

## FLEXIBLE BATTERY / STARTER CABLE

Specification:  
 Conductor: 196/0.4  
 Amp Cap: 170  
**TW 800551**  
 Cross Section:  
 Area: 25sq.mm  
 Nominal O/D: 9.8mm  
 E3010 **9.97 per mtr**  
 Usage:  
 Battery starter

Specification:  
 Conductor: 315/0.40  
 Amp Cap: 300  
**TW800561**  
 Cross Section:  
 Area: 40sq.mm  
 Nominal O/D: 12.2mm  
 E3011 **15.64 per mtr**  
 Usage:  
 Battery starter, winches



Specification:  
 Conductor: 396/0.40  
 Amp Cap: 345  
**TW 800571**  
 Cross Section:  
 Area: 50sq.mm  
 Nominal O/D: 13.3mm  
 E3012 **16.95 per mtr**  
 Usage:  
 Battery starter, winches



Specification:  
 Conductor: 475/0.40  
 Amp Cap: 415  
**TW800581**  
 Cross Section:  
 Area: 60sq.mm  
 Nominal O/D: 14.6mm  
 E3013 **20.18 per mtr**  
 Usage:  
 Battery starter, winches



Specifications  
 Conductor: 905/0.30  
 Amp Cap: 485  
**TW800591**  
 Cross Section:  
 Area: 70sq.mm  
 Nominal O/D: 15.4mm  
 E3014 **22.16 per mtr**  
 Usage:  
 Heavy duty



Specification:  
 Conductor: 684/0.4  
 Amp Cap: 500  
**TW800601**  
 Cross Section:  
 Area: 95sq.mm  
 Nominal O/D: 17.9mm  
 E3015 **30.35 per mtr**  
 Usage:  
 Suggestions: Heavy duty

## TWIN CABLE THIN WALL



Specification:  
 Conductor: 2 x 32/0.20  
Amp Cap: 16.5  
**TW800833**  
 Cross Section:  
 Area: 2 x 1.0sq.mm  
 Nominal O/D: 3.5 x 5.5mm  
 Usage:  
 Interior and navigation lights  
 E3021 **1.11** per mtr  
 E3021 **37.30** 30mtr coil



Specification:  
 Conductor: 2 x 28/0.30  
Amp Cap: 25.0  
**TW800843**  
 Cross Section:  
 Area: 2 x 2.0sq.mm  
 Nominal O/D: 3.8 x 6.6mm  
 Usage:  
 Searchlights etc.  
 E3022 **1.85** per mtr  
 E3022 **55.50** 30mtr coil



Specification:  
 Conductor: 2 x 44/0.30  
 Amp Cap: 27.50  
 Cross Section:  
 Area: 2 x 3.0sq.mm  
 Nominal O/D: 4.4x 7.6mm  
 Usage:  
 Suggestions: Battery feed.  
 E3023 **3.09** per mtr  
 E3023 **97.38** 30mt coil